
PRODUCT SUBMITTAL

#1100 Triangular Tie





The #1100 Triangle is used in conjunction with the TypeIII Screw-On Veneer Anchor for anchoring brick veneer to metal stud.

Brick Institute of America and ACI 530 do not recommend ties with formed drips. Tests have shown that drips can reduce the ultimate buckling load by approximately 50%.

MATERIAL CONFORMANCE

Wire (Carbon Steel): Prefabricated from cold-drawn steel wire conforming to ASTM A1064/A1064M, ASTM A82/ A82M

Tensile Strength - 80,000 p.s.i. | Yield Point - 70,000 p.s.i. minimum

ASTM A951/A951M (Standard Specification for Steel Wire for Masonry Joint Reinforcement)

ACI / ASCE 530 (Building Code Requirements for Masonry Structures)

Mill Galvanized coating: ASTM A641/A641M (0.1 oz/ft)

Hot-Dip Galvanized after fabrication: ASTM A153/A153M-B2 (1.5 oz/ft)

Wire (Stainless Steel): **ASTM A580/ASTM 580M - AISI** Type 304 (Type 316 available on special orders)



Recycled Content:

Mill Galvanized & Fot Dipped, 82.8% Post-Consumer 17% Post Industrial / Pre Consumer

Stainless Steel

97% Pre-Consumer V O C Content - 0%

SIZES / FINISHES

1100 Triangle Diameter: # 1100 Triangle Size:

3/16" 3" x 3" 6" x 6" 1/4" 4" x 4" 7" x 7" 5" x 5" 7" x 9"

Other

WIRE BOND Clip: Straight & Cut Seismic Wire:

16 gauge 10'-0" Lengths

9 gauge 3/16" diameter

Finishes:

Mill Galvanized Hot Dip Galvanized Stainless Steel

Corporate Office: 400 Rountree Rd Charlotte, NC 28217

TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113

TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113