

LEED MATERIAL INFORMATION



WIRE-BOND

INNOVATION IN MASONRY
CONSTRUCTION

Date:	
Submittal Number:	

GENERAL PRODUCT INFORMATION

Product:	BOND -N- FLASH SA
Manufacturer:	WIRE-BOND
Total Product Cost:	

PROJECT INFORMATION

Project Name:		
Location:		
Subcontractor:		

LEED Product Qualification Data

Thermal & Moisture Protection
Flexible Membrane Flashing 07 65 00

BOND-N-FLASH S.A. Flexible Stainless Steel Flashing meets the following criteria for MR 4.1:
Composition of product: a layer of stainless steel, a layer of IISRP adhesive , a layer of release liner

Stainless Steel	02% Virgin Material
Stainless Steel	16% Post Industrial Recycled Content
IISRP Compound	50% Virgin Material
IISRP Compound	05% Post Industrial Recycled Content
Polypropylene Liner	13% Virgin Material
Polypropylene Liner	08% Post Industrial Recycled Content
Polypropylene Liner	06% Post Consumer Recycled Content

EMBODIED ENERGY:

Product does not use an adhesive which needs to be stored in a liquid state which requires a constant 24 hr. energy usage.

Total Post Industrial Recycled Content 29%
Total Post Consumer Recycled Content 6%

BOND-N-FLASH S.A.: Flexible Stainless Steel Flashing meets the following criteria for MR 5.1 and 5.2:
If within a 500 mile radius of:

Clark/Hammerbeam Corporation
1700 London Road
Cleveland, OH 44112

Mileage to
Jobsite

CERTIFIED BY (Installer / Manufacturer)

Date:

Print Name: _____

Signature: _____

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113