

PRODUCT SUBMITTAL

WIRE-BOND

Aqua Flash Latex Primer



DESCRIPTION

AQUA FLASH Primer is a one component water-based high tack primer specifically designed to promote maximum adhesion of the AQUA FLASH waterproofing membrane on all vertical and horizontal surfaces. May be applied to concrete, block, brick wood, metal, and gypsum.

APPLICATION INSTRUCTIONS

Substrate surface should be dry, free from oil and grease or any loose debris of any kind. Primer should be stirred in the container and applied either with a soft bristle brush or suitable spray equipment. Allow Primer to dry prior to application of the waterproofing membrane.

PHYSICAL PROPERTIES:

Weight	9 lbs.
Total solids	49%
Dry time (75°F % 50% Humidity)	4 hrs.
Flammability (Wet)	Non-flammable
Application Temperature	>40°F

SPECIFICATION: Meets **ASTM D 1227-82 TYPE III**

COVERAGE: 50 square feet/gallon depending on the porosity and condition of the substrate

CLEAN-UP: Wet primer can be cleaned up with soap and water. If primer has dried, mineral spirits or paint thinner may be used

Packaging: 5 gallon

Storage

Product needs to be stored above 40°F.

Product Information: All users of the *AQUA FLASH* products should read the Safety Data Sheets (SDS) which are available from WIRE-BOND

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113