

# PRODUCT SUBMITTAL

WIRE-BOND


## # 4200 Termination Bar



Termination Bar



Flashing

MATERIAL CONFORMANCE	SIZES / FINISHES
<p><b>SHEET METAL:</b></p> <p>Stainless Steel Type 304: <b>ASTM A240/A240M, ASTM 666, ASTM A480/A480M and ASTM A167</b> (Type 316 available on special orders)</p> <p>Aluminum: <b>ASTM B221 / ASTM B221M</b></p>  <p><b>Steel Products (flats) Recycled Content:</b>                      Stainless Steel, 60% Post Consumer                      Aluminum 18% average (10% - 25% Range) Post Consumer                      56% average (25% - 75% Range) Pre Consumer</p> <p>V O C Content - 0%</p>	<p><b>#4200 Termination Bar:</b></p> <p><b>Stainless Steel:</b>                      1/8" x 1" wide x 10'-0"</p> <p><b>5/16" Slotted holes:</b> 16" O.C. 8" O.C. 6" O.C.</p> <p><b>Aluminum:</b>                      1/8" x 1" wide x 10'-0"</p> <p><b>3/8" Slotted holes:</b> 16" O.C. 8" O.C.</p>

**Corporate Office:** 400 Rountree Rd Charlotte, NC 28217  
 TEL: (800) 849-6722 FAX: (704) 525-3761

**Mailing Address:** P.O. Box 240988 Charlotte, NC 28224



[www.wirebond.com](http://www.wirebond.com)

**Memphis Plant:** 2365 Harbor Ave. Memphis, TN 38113  
 TEL: (800) 441-8359 FAX: (901) 775-9449

**Mailing Address:** P.O. Box 13124 Memphis, TN 38113